

Rimlex® 310

Technical Data Sheet



Rimlex® 310 is a room temperature vulcanising (RTV) silicone sealant which has been specifically developed for high temperature applications. Once applied the compound reacts with atmospheric moisture to form a tough and durable rubber seal. It has excellent adhesion to metals, glass, ceramics and plastics. The compound has large gap filling properties which makes it ideal for application to non machined surfaces and even as cast surfaces.

Rimlex 310 is a general purpose adhesive sealant with many applications in building, engineering and the automotive industry. It has excellent adhesion without primer to metals, glass, ceramics and most rigid plastics. The cured compound is resistant to weathering, aging and to many solvents, oil, water and lubricants. Its excellent thermal stability means it can be used for sealing and bonding at temperatures up to 300°C (570°F) and for gasketing up to 350°C (660°F) depending on the application. It is ideal for use as a flexible gasket or flange sealant in general engineering and automotive applications (i.e. approved to specifications including JLR STJLR.60.5020.X202).



PROPERTIES (CURED)

Colour	Brick Red
Hardness (Shore A)	43 (approximately)
Sealing pressure:	>150 bar
Shelf life on components	Indefinite
Re-usability	Dependent upon application
Temperature range	-50 (-60) to 300°C (570°F) (350°C (660°F) gasketing, 460°C (860°F) ignition temperature)
Shrinkage	3%
Elongation at break DIN 53504 S3A	420%
E modulus@ 100% elongation	0.6N/mm ²

Information presented in this data sheet is considered reliable but conditions and methods of use, which are beyond our control, may modify results. Before these products are used, the user should confirm suitability.

We cannot accept liability for any loss, injury or damage which may result from its use to the full extent permitted by law.

We do not warrant the accuracy or completeness of any such information, whether orally or in writing.

We reserve the right at any time and without notice to update or improve products and processes and our information concerning the same.



Inlex Locking Ltd
Wood Lane, Fordhouses,
Wolverhampton WV10 8HN
+44 (0)1902 397300
anochrome.com



Anocote Czech Republic o.s.
Nachodská 626, Platište nad Labem,
50301 Hradec Králové, Czech Republic
+420 495 221 331
anocote.cz



Anocote Polska Sp. z o.o.
ul. Podzwierzyniec 41
37-100 Łañcut
+48 172 258 539
anocote.pl